

RubberCover Water Based Bonding Adhesive

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : RubberCover Water Based Bonding Adhesive
Registration number REACH : Not applicable (mixture)
Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Adhesive
 Professional use
 Construction

1.2.2 Uses advised against

General population
 Other non-specified uses are excluded

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Holcim Solutions and Products EMEA
 Ikaroslaan 75
 B-1930 Zaventem
 ☎ +32 2 711 44 50
 compliance-emea-hbe@holcim.com

1.4. Emergency telephone number

24h/24h :
 +32 14 58 45 45 (BIG)
 24h/24h
 Ireland - Beaumont Hospital, Dublin (NPIC): +353 1 809 2166 (Public 8 am- 10 pm)
 Ireland - Beaumont Hospital, Dublin (NPIC): +353 1 809 2566 (Professionals)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Skin Sens.	category 1	H317: May cause an allergic skin reaction.
Aquatic Chronic	category 3	H412: Harmful to aquatic life with long lasting effects.

2.2. Label elements



Contains: reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1).

Signal word Warning

H-statements

H317 May cause an allergic skin reaction.
 H412 Harmful to aquatic life with long lasting effects.

P-statements

P280 Wear protective gloves, protective clothing and eye protection/face protection.
 P273 Avoid release to the environment.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P302 + P352 IF ON SKIN: Wash with plenty of water and soap.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

Caution! Substance is absorbed through the skin

RubberCover Water Based Bonding Adhesive

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No List No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) 01-2120764691-48	55965-84-9 911-418-6	C<0.005%	Acute Tox. 2; H330 Acute Tox. 2; H310 Acute Tox. 3; H301 Skin Sens. 1A; H317 Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 Skin Irrit. 2; H315: 0,06% ≤C<0.6%, (CLP Annex VI (ATP 0)) Eye Dam. 1; H318: C≥0,6%, (CLP Annex VI (ATP 13)) Skin Corr. 1B; H314: C≥0,6%, (CLP Annex VI (ATP 0)) Eye Irrit. 2; H319: 0,06% ≤C<0,6%, (CLP Annex VI (ATP 0)) Skin Sens. 1A; H317: C≥0,0015%, (CLP Annex VI (ATP 13))	(1)(2)(10)	Constituent	M: 100 (Acute, ECHA (registration dossier)) M: 100 (Chronic, ECHA (registration dossier))

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

No effects known.

After skin contact:

No effects known.

After eye contact:

No effects known.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

Publication date: 2023-06-29

RubberCover Water Based Bonding Adhesive

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2 extinguisher.

Major fire: Class B foam (not alcohol-resistant).

5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion.

Major fire: Water; risk of puddle expansion.

5.2. Special hazards arising from the substance or mixture

In case of fire: possible release of toxic/corrosive gases/vapours.

5.3. Advice for firefighters

5.3.1 Instructions:

Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Face shield (EN 166). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No naked flames.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Face shield (EN 166). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Contain released product, collect/pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill. Prevent soil and water pollution. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into inert absorbent material, e.g.: sand, saw dust, kieselguhr. Scoop absorbed substance into closing containers.

Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Keep away from naked flames/heat. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks. Observe very strict hygiene - avoid contact. Remove contaminated clothing immediately. Keep container tightly closed. Do not discharge the waste into the drain.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Meet the legal requirements. Provide for a tub to collect spills.

7.2.2 Keep away from:

Heat sources, (strong) acids, (strong) bases, oxidizing agents, reducing agents.

7.2.3 Suitable packaging material:

No data available

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

RubberCover Water Based Bonding Adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

Austria

5-Chlor-2-methyl-2,3- dihydroisothiazol-3-on und 2-Methyl-2,3-di-hydroisothiazol- 3-on (Gemisch im Verhältnis 3:1)	Tagesmittelwert (MAK)	0.05 mg/m ³
--	-----------------------	------------------------

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

If applicable and available it will be listed below.

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term local effects inhalation	0.02 mg/m ³	
	Acute local effects inhalation	0.04 mg/m ³	

DNEL/DMEL - General population

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term local effects inhalation	0.02 mg/m ³	
	Acute local effects inhalation	0.04 mg/m ³	
	Long-term systemic effects oral	0.09 mg/kg bw/day	
	Acute systemic effects oral	0.11 mg/kg bw/day	

PNEC

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Compartments	Value	Remark
Fresh water	3.39 µg/l	
Fresh water (intermittent releases)	3.39 µg/l	
Marine water	3.39 µg/l	
Marine water (intermittent releases)	3.39 µg/l	
STP	0.23 mg/l	
Fresh water sediment	0.027 mg/kg sediment dw	
Marine water sediment	0.027 mg/kg sediment dw	
Soil	0.01 mg/kg soil dw	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

8.2.2 Individual protection measures, such as personal protective equipment

Observe very strict hygiene - avoid contact. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Thickness	Protection index	Remark
viton	> 480 minutes	0.5 mm	Class 6	
nitrile rubber	> 240 minutes	0.4 mm	Class 5	

c) Eye protection:

Face shield (EN 166).

d) Skin protection:

Protective clothing (EN 14605 or EN 13034).

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

Publication date: 2023-06-29

RubberCover Water Based Bonding Adhesive

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Liquid
Odour	Characteristic odour
Odour threshold	No data available in the literature
Colour	White
Particle size	Not applicable (liquid)
Explosion limits	No data available in the literature
Flammability	Not classified as flammable
Log Kow	Not applicable (mixture)
Dynamic viscosity	40000 mPa.s ; 40 °C
Kinematic viscosity	No data available in the literature
Melting point	No data available in the literature
Boiling point	100 °C
Relative vapour density	No data available in the literature
Vapour pressure	No data available in the literature
Solubility	Water ; insoluble
Relative density	1 - 1.1
Absolute density	1000 kg/m ³ - 1100 kg/m ³ ; No data available in the literature
Decomposition temperature	No data available in the literature
Auto-ignition temperature	No data available in the literature
Flash point	No data available in the literature
pH	7 - 8

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Heating increases the fire hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Keep away from naked flames/heat. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks.

10.5. Incompatible materials

(strong) acids, (strong) bases, oxidizing agents, reducing agents.

10.6. Hazardous decomposition products

No data available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

RubberCover Water Based Bonding Adhesive

No (test)data on the mixture available

Judgement is based on the relevant ingredients

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	66 mg/kg bw		Rat (male / female)	Experimental value	Calculated by reference to active substance
Dermal	LD50	OECD 402	> 141 mg/kg bw	24 h	Rat (male / female)	Experimental value	
Inhalation (dust)	LC50	OECD 403	0.17 mg/l air	4 h	Rat (male / female)	Experimental value	Calculated by reference to active substance

Publication date: 2023-06-29

RubberCover Water Based Bonding Adhesive

Conclusion

Not classified for acute toxicity

Corrosion/irritation

RubberCover Water Based Bonding Adhesive

No (test)data on the mixture available

Judgement is based on the relevant ingredients

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Serious eye damage			1; 24; 48; 72 hrs; 7; 14 days	Rabbit	Experimental value	Single treatment with rinsing
Skin	Corrosive	OECD 404	4 h		Rabbit	Experimental value	Aqueous solution

Conclusion

Not classified as irritating to the respiratory system

Not classified as irritating to the skin

Not classified as irritating to the eyes

Respiratory or skin sensitisation

RubberCover Water Based Bonding Adhesive

No (test)data on the mixture available

Classification is based on the relevant ingredients

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

Conclusion

May cause an allergic skin reaction.

Not classified as sensitizing for inhalation

Specific target organ toxicity

RubberCover Water Based Bonding Adhesive

No (test)data on the mixture available

Judgement is based on the relevant ingredients

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (diet)	NOAEL systemic effects	OECD 409	22 mg/kg bw/day		No adverse systemic effects	13 weeks (7 days / week)	Dog (male / female)	Experimental value
Dermal	NOAEL systemic effects	EPA OPP 82-3	2.625 mg/kg bw/day		No adverse systemic effects	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Dermal	NOAEC local effects	EPA OPP 82-3	0.105 mg/kg bw/day	Skin	No effect	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (aerosol)	NOAEL	OECD 413	0.34 mg/m ³ air		No effect	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

RubberCover Water Based Bonding Adhesive

No (test)data on the mixture available

Judgement is based on the relevant ingredients

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Result	Method	Test substrate	Effect	Value determination	Remark
Positive with metabolic activation, positive without metabolic activation	EPA OPP 84-2	Bacteria (S. typhimurium and E. coli)		Experimental value	Aqueous solution
Positive with metabolic activation, positive without metabolic activation	OECD 476	Mouse (lymphoma L5178Y cells)		Experimental value	Aqueous solution

Mutagenicity (in vivo)

Publication date: 2023-06-29

RubberCover Water Based Bonding Adhesive

RubberCover Water Based Bonding Adhesive

No (test)data on the mixture available

Judgement is based on the relevant ingredients

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Oral (stomach tube))	EPA OPP 84-2	2 dose(s)/24-hour interval	Mouse (male / female)		Experimental value

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

RubberCover Water Based Bonding Adhesive

No (test)data on the mixture available

Judgement is based on the relevant ingredients

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Oral (drinking water)	NOEL	OECD 453	300 ppm	24 month(s)	Rat (male / female)	No carcinogenic effect		Experimental value

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

RubberCover Water Based Bonding Adhesive

No (test)data on the mixture available

Judgement is based on the relevant ingredients

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	EPA OPP 83-3	≥ 19.6 mg/kg bw/day	10 days (gestation, daily)	Rat	No effect		Experimental value
Maternal toxicity (Oral (stomach tube))	LOAEL	EPA OPP 83-3	28 mg/kg bw/day	10 days (gestation, daily)	Rat	Maternal toxicity		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL	OECD 416	30 ppm	10 week(s)	Rat (male / female)	No effect		

Conclusion

Not classified for reprotoxic or developmental toxicity

Aspiration hazard

Judgement is based on the relevant ingredients

Not classified for aspiration toxicity

Toxicity other effects

RubberCover Water Based Bonding Adhesive

No (test)data on the mixture available

Chronic effects from short and long-term exposure

RubberCover Water Based Bonding Adhesive

Skin rash/inflammation.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

RubberCover Water Based Bonding Adhesive

No (test)data on the mixture available

Classification is based on the relevant ingredients

Publication date: 2023-06-29

RubberCover Water Based Bonding Adhesive

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	EPA OPP 72-1	0.19 mg/l	96 h	Oncorhynchus mykiss	Flow-through system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EC50		0.007 mg/l	48 h	Acartia tonsa		Salt water	Experimental value; GLP
Toxicity algae and other aquatic plants	NOEC	OECD 201	0.49 µg/l	48 h	Skeletonema costatum	Static system	Salt water	Experimental value; Growth rate
	ErC50	OECD 201	19.9 µg/l	72 h	Skeletonema costatum	Static system	Salt water	Experimental value; GLP
Long-term toxicity fish	NOEC	OECD 210	46.4 µg/l	35 day(s)	Danio rerio	Flow-through system	Fresh water	Experimental value; GLP
Long-term toxicity aquatic crustacea	NOEC	EPA OPP 72-4	0.1 mg/l	21 day(s)	Daphnia magna	Flow-through system	Fresh water	Experimental value; Nominal concentration

Conclusion

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Biodegradation water

Method	Value	Duration	Value determination
OECD 301B	48 % - 56 %; GLP	28 day(s)	Experimental value

Conclusion

Water

Contains traces of a non-biodegradable component

12.3. Bioaccumulative potential

RubberCover Water Based Bonding Adhesive

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	OECD 305	41 - 54; Fresh weight	28 day(s)	Lepomis macrochirus	Experimental value

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		-0.32 - 0.7	20 °C	Experimental value

Conclusion

Does not contain bioaccumulative component(s)

12.4. Mobility in soil

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

(log) Koc

Parameter	Method	Value	Value determination
Koc	OECD 106	6.4 - 10	Experimental value
log Koc		0.81 - 1	Calculated value

Conclusion

Contains component(s) with potential for mobility in the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

12.7. Other adverse effects

RubberCover Water Based Bonding Adhesive

Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

Publication date: 2023-06-29

RubberCover Water Based Bonding Adhesive

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Groundwater

Groundwater pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Can be considered as non hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 10 (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants other than those mentioned in 08 04 09). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

No data available

SECTION 14: Transport information

Road (ADR)

14.1. UN number

Transport	Not subject
-----------	-------------

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Hazard identification number	
Class	
Classification code	

14.4. Packing group

Packing group	
Labels	

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	
Limited quantities	

Rail (RID)

14.1. UN number

Transport	Not subject
-----------	-------------

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Hazard identification number	
Class	
Classification code	

14.4. Packing group

Packing group	
Labels	

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	
Limited quantities	

Inland waterways (ADN)

14.1. UN number/ID number

UN number/ID number	9006
---------------------	------

14.2. UN proper shipping name

Proper shipping name	environmentally hazardous substance, liquid, n.o.s.
----------------------	---

14.3. Transport hazard class(es)

Class	9
Classification code	M12

14.4. Packing group

Packing group	
Labels	

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

Publication date: 2023-06-29

RubberCover Water Based Bonding Adhesive

14.6. Special precautions for user

Special provisions	
Limited quantities	

Sea (IMDG/IMSBC)

14.1. UN number

Transport	Not subject
-----------	-------------

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Class	
-------	--

14.4. Packing group

Packing group	
Labels	

14.5. Environmental hazards

Marine pollutant	
Environmentally hazardous substance mark	no

14.6. Special precautions for user

Special provisions	
Limited quantities	

14.7. Maritime transport in bulk according to IMO instruments

Annex II of MARPOL 73/78	Not applicable, based on available data
--------------------------	---

Air (ICAO-TI/IATA-DGR)

14.1. UN number/ID number

Transport	Not subject
-----------	-------------

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Class	
-------	--

14.4. Packing group

Packing group	
Labels	

14.5. Environmental hazards

Environmentally hazardous substance mark	no
--	----

14.6. Special precautions for user

Special provisions	
--------------------	--

Passenger and cargo transport

Limited quantities: maximum net quantity per packaging	
--	--

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
< 0.2 %	

Directive 2012/18/EU (Seveso III)

Not subject to registration according to Directive 2012/18/EU (Seveso III)

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Substances falling within one or more of the following points: (a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008: — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation — skin sensitiser category 1, 1A or 1B — skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2 — serious eye damage category 1 or eye irritant category 2 (b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081

Publication date: 2023-06-29

RubberCover Water Based Bonding Adhesive

Parliament and of the Council (c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex. The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.

National legislation Belgium

RubberCover Water Based Bonding Adhesive

No data available

National legislation The Netherlands

RubberCover Water Based Bonding Adhesive

Waterbezwaarlijkheid	A (3); Algemene Beoordelingsmethodiek (ABM)
----------------------	---

National legislation France

RubberCover Water Based Bonding Adhesive

No data available

National legislation Germany

RubberCover Water Based Bonding Adhesive

WGK	2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
-----	--

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

TA-Luft	5.2.5/l
---------	---------

National legislation Austria

RubberCover Water Based Bonding Adhesive

No data available

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Gefahr der Sensibilisierung der Haut	5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on (Gemisch im Verhältnis 3:1); Sh
--------------------------------------	---

National legislation United Kingdom

RubberCover Water Based Bonding Adhesive

No data available

Other relevant data

RubberCover Water Based Bonding Adhesive

No data available

15.2. Chemical safety assessment

No chemical safety assessment is required for a mixture.

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

H301 Toxic if swallowed.
H310 Fatal in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H330 Fatal if inhaled.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH071 Corrosive to the respiratory tract.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BEI	Biological Exposure Indices
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC10	Effect Concentration 10 %
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
GLP	Good Laboratory Practice
LCO	Lethal Concentration 0 %

Publication date: 2023-06-29

RubberCover Water Based Bonding Adhesive

LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
LOAEC/LOAEL	Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level
NOAEC/NOAEL	No Observed Adverse Effect Concentration/No Observed Adverse Effect Level
NOEC/NOEL	No Observed Effect Concentration/No Observed Effect Level
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Publication date: 2023-06-29